

PRODUCT SPECIFICATIONS FOR CB24B

WEIGHTS

| | |
|-------------------------------------|-----------|
| Operating Weight | 6003.0 lb |
| Maximum Weight at Front Drum | 2857.0 lb |
| Maximum Weight at Rear Drum | 3147.0 lb |

OPERATING SPECIFICATIONS

| | |
|--|------------|
| Standard Compaction Width | 47.0 in |
| Curb Clearance | 20.0 in |
| Turning Radius - Inside Drum Edge | 8.0 ft |
| Ground Clearance | 11.0 in |
| Travel Speed - Maximum | 7.5 mile/h |
| Static Linear Load | 63.0 lb/in |

ENGINE

| | |
|---------------------|---------|
| Gross Power | 36.2 HP |
| Engine Model | C1.5 |

DIMENSIONS

| | |
|-------------------------------|----------|
| Overall Length | 101.0 in |
| Wheel Base | 71.0 in |
| Overall Width | 52.0 in |
| Maximum Machine Height | 106.0 in |

| | |
|----------------------|---------|
| Drum Diameter | 28.0 in |
| Drum Width | 47.0 in |

VIBRATORY SYSTEM

| | |
|---|------------------------------------|
| Centrifugal Force per Drum - Minimum | 3282.0 lb |
| Centrifugal Force per Drum - Maximum | 7374.0 lb |
| Nominal Amplitude - High | 0.021 in |
| Frequency | 63/55/42 Hz (3,780/3,300/2520 vpm) |

SERVICE REFILL CAPACITIES

| | |
|----------------------------------|---------------|
| Fuel Tank Capacity | 17.0 gal (US) |
| Water Spray Tank Capacity | 62.0 gal (US) |

CB24B OPTIONAL EQUIPMENT

ANTI-FREEZE SYSTEM

BALLAST

BATTERY DISCONNECT SWITCH

BIO-HYDRAULIC OIL

FOLDABLE CANOPY

FIXED CANOPY

DUAL PROPEL LEVERS

NON-SUSPENSION SEAT

PRODUCT LINK

FIXED ROPS

FOLDABLE ROPS

SEAT W/OPERATOR PRESENCE SWITCH

SLIDING SEAT

TRACTION CONTROL

